

Parts Washers

Conveyer Style



OLD VALUES. NEW IDEAS.



Continuous cleaning
of parts on a conveyer
system, ideal for industrial
cleaning of newly machined items.

CONVEYER STYLE PARTS WASHER SPECIFICATIONS

MODEL	AL1516C	AL1924C
WORKING WIDTH	16"	24"
WORKING HEIGHT	15"	19"
OVERALL HEIGHT	72"	72"
OVERALL WIDTH	60"	60"
OVERALL LENGTH	87"	150"
LOAD CAPACITY	500 lb.	500 lb.
SOLUTION CAPACITY	190 Gal.	220 Gal.
NOZZLES	44	62
PUMP MOTOR	5 HP, Cast Iron Vertical Sealless Pump	7.5 HP, Cast Iron Vertical Sealless Pump
CONVEYER MOTOR	1/4 HP Chain Driven	1/4 HP Chain Driven
PUMP CAPACITY	70 GPM@55 PSI	150 GPM@55 PSI
ELECTRIC WASH HEATER	18 KW Heater	18 KW Heater
VOLTAGE	240 V/60 HZ/3 PH	240V/60 HZ/3 PH
TANK DEBRIS SCREEN	180 sq. in.	180 sq. in.
HEAT CONTROL	175°F, Process heat controlled with digital readout	175°F, Process heat controlled with digital readout
OIL SKIMMER	Stainless disc style	Stainless disc style
CONSTRUCTION	10 gauge tank, 12 gauge door and cabinet steel plate	10 gauge tank, 12 gauge door and cabinet steel plate
SHIPPING WEIGHT	2000 lb	2500 lb

STANDARD OPTIONS

- Removable Access Service Panels
- Low Water Shut off
- Adjustable Conveyor Speed Rate, 0-15' per minute
- 6" Diameter Cabinet Vent with Steam Hood

OPTIONS AVAILABLE

- 24-hour, 7-day Heater Timer
- 24-hour, 7-day Skimmer Timer
- Auto Refill
- Installed Tank Insulation
- Soap Injection System
- Electric Eye Conveyor Stop
- Air Blower System
- FR-1 Filter Ready Plumbing
- F-1 Filter System
- Stainless Steel Options for Cabinet, Tank, Hood, Plumbing, Spray Nozzles
- Custom Load & Width Specifications Available
- Natural/LP Gas Heat
- 480 V/60 HZ/3 PH Voltage



OLD VALUES. NEW IDEAS.

