

**Hydroblaster™ E Series**

MODEL	3/1000	4/1000	4/2000	4/3000	5/3000	5/5000	10/3000
VOLUME (GPM)	3	4	4	4	5	5	10
PRESSURE (PSI)	1000	1000	2000	3000	3000	5000	3000
ELECTRIC MOTOR(HP)	2	3	5	7.5	10	20	20
VOLTAGE <sup>1</sup> (STD)	(A), B,C,D	(B), C, D	(B), C, D	B,(C), D	(C), D	(C), D	(C), D
AMPERAGE	17, 9, 5, 3	16, 8, 4	25, 14, 7	36,28,14	28, 14	55, 35	55, 35
DEMINSIONS	31 ½ L X 24W X 40 1/8H						38L X 27W X 41 ¼ H
WEIGHT (LBS)	386	386	386	428	444	650	650

<sup>1</sup> Voltage codes: A=110 volt single phase, B=230 volt single phase, C=230 volt three phase, D=460 volt three phase.



Shown with options

**Standard Features:**

- Heavy duty electric motor with reset on all 1 phase
- Belt drive
- Full equipment covers
- Trigger gun with insulated variable pressure wand
- 15 degree nozzle
- 50' hose rated 3000 PSI
- Downstream chemical injection

Part#	Description
	<b>Electrical: Power &amp; Controls</b>
2AT717	115 Volt (model 3/1000 only)
2AT718	230 Volt Single Phase (model 4/1000, 4/2000, 4/3000)
2CF092	208-230V,3PH,Mag Starter,24Volt (model 5/3000, 5/5000, 10/3000)
2CF093	460V,3PH,Mag Starter,24Volt (model 5/3000, 5/5000, 10/3000)
2CE089	Shut Down Timer
	<b>*Remote Options</b>
1XG805	Trigger Actuated Start
1UF029	Remote On/Off
1UF031	Remote On/Off, Explosion Proof
	<b>Hour Meter Option</b>
2FQ988	Hour Meter Opt., 24V, E.
	<b>Finish Options</b>
1UP111	Painted Trim
1UP112	Stainless Trim
	<b>Discharge Options</b>
1XH816	Single High Pressure Nozzle, 15 Deg
1XH817	Four Nozzle Kit, 0,15,25,40 Deg
1XH818	Hose Reel Kit, Wall Mount.
2FV036	Hose Reel Kit, Machine Mount.
	<b>System Gauge Options</b>
2CE085	Pressure Gauge
	<b>Inlet Options</b>
1UP115	Breaker Tank, Plastic
1UP116	Breaker Tank, Stainless Steel
1XL855	Breaker Tank (Model 10/3000 only)

NOTE: \* reflects the standard