

Hydroblaster™ GSOV Series

PART #	3.5/3000GSOV	5/3000GSOV
VOLUME (GPM)	3.5	5.0
PRESSURE (PSI)	3000	3000
GASOLINE ENGINE (HP)	12	18
BTU (PER HOUR X 1000)	315	440
WEIGHT (LBS)	580	618
FUEL TANK (Gal)	8 oil, 1.5 gas	8 oil, 8 gas
DIMENSIONS	45 ¼" long X 26" wide X 55 ¼" high	



Standard Features:

- Extremely portable 4 pneumatic wheels, tilt back design.
- Schedule 80 steel coil
- Direct drive pumping system
- Trigger gun
- Insulated variable pressure wand
- 15 degree nozzle
- 50' hose rated 3000 PSI
- Downstream chemical injection

Part#	Description
	Temperature Controls
*1SP592	High Limit Temperature Switch, 225°F
2BY021	Thermostat, Adj.85-250°F, Rotary Switch
	Steam Discharge Options
2BK888	Steam Combo
	Engine: Power & Controls
2DY548	Kohler 12HP, Electric Start, Gas (model 3.5/3000)
2BK889	Kohler 18 HP, Electric Start (model 5/3000)
2GJ178	Honda 20 HP, Electric Start (model 5/3000)
	Engine: Battery Options
*1YG062	No Battery
1YG063	Battery, Liquid Acid, Non Shippable
	Gauge & Meter Options
1WR655	Pressure Gauge, Pipe Mounted, 5000 PSI
1UF037	Temperature Gauge
2BL891	Hour Meter
	Frame Options
*2BL892	Painted Trim
2BL893	Stainless Trim
	Discharge Options
*1XM862	Single High Pressure Nozzle, 15 Deg
1XM861	Four Nozzle Kit, 0,15,25,40 Deg
1YG061	Turbo Nozzle
2BL895	Hose Reel Kit

NOTE: * reflects the standard