

Hydroblaster™ Single Axle Trailers

Standard Features:

- Factory engineered integrating both the Hydroblaster pressure washer and water tank into a total system design
- 3", 4" & 6" channel iron construction
- Swing jack with platform foot
- Dual safety chains
- 12 Volt, D.O.T. approved light package

Choose your options (STD- designates the standard)

Trailer Size Options

- STD** -Single Trailer, 125 Gallon Tank, No Brakes
- OPT**-Single Trailer, 125Gallon Tank, Electric Brakes
- OPT**-Single Trailer, 225 Gallon. Tank, No Brakes
- OPT**-Single Trailer, 225 Gallon. Tank, Electric Brakes
- OPT**-Single Trailer, 225GallonTank, Hydraulic Brakes

Trailer Hitch Options

- STD** - Coupler, A-Frame, Ball, 2"
- OPT**- Coupler,A-Frame,Ball,2",Hydraulic Brakes
- OPT**- Coupler, A-Frame, Lunette Eye

Trailer Light Options

- STD** - Lights, Trailer, 12 Volt
- OPT**- Lights, Trailer, 24 Volt

Tire And Wheel Options

- STD** - Wheels and Tires, 13", Single Axle
- OPT**- Wheels and Tires, 15", Single Axle (STD on TS225)
- OPT**- Spare Tire with trailer mount, 13"
- OPT**- Spare Tire with trailer mount, 15"

Trailer Extension Options

- STD** - No Extension
- OPT**- Extension, 2' on rear of trailer

Trailer Accessory Options

- OPT**- Prespray System, 12 Volt, With 30 Gallon Tank
- OPT**- Soap Tank, 30 Gal., To Injector
- OPT**- Hose Reel, Inlet Water
- OPT**- Hose Reel, Prespray

Hose Options, Low Pressure

- OPT**- Prespray Hose, 1/2", 50'
- OPT**- Prespray Hose, 1/2", 100'
- OPT**- Inlet Water Hose, 5/8", 50'.
- OPT**- Inlet Water Hose, 5/8", 100'.



865 West 2600 South, Salt Lake City, UT 84119
Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com